



PRICE LIST – DEALER TESTING AND MEASURING INSTRUMENTS



+60 YEARS
ONE MISSION



Reliable



Long-Lasting




Affordable



ISO 9001:2015 CERTIFICATE



EIL APPROVAL



STQC TYPE TEST REPORT



PGCIL APPROVAL

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
1A	Digital Multi-Range Portable Meter				
1	5 Digit AC TRMS Multi-Range Voltmeter , 0 - 200mV, 0 - 2V, 0 - 20V, 0 - 200V and 0 - 750V with Backlight Display , USB Port (Standard) and User Interface Software (Optional), Data Hold, APO, Low Battery Indication, Overload Indication, Strong Rugged Casing with Tilt Stand With Calibration Certificate with Traceability to NABL Lab will be supplied with every meter.	MIPL	9030 3310	PM-VAC-5R	2790
2	5 Digit DC Multi-Range Voltmeter , 0 - 200mV, 0 - 2V, 0 - 20V, 0 - 200V and 0 - 1000V with Backlight Display , USB Port (Standard) and User Interface Software (Optional), Data Hold, APO, Low Battery Indication, Overload Indication, Strong Rugged Casing with Tilt Stand. With Calibration Certificate with Traceability to NABL Lab will be supplied with every meter.	MIPL	9030 3310	PM-VDC-5R	2700
3	5 Digit AC TRMS Multi-Range Ammeter , 0 - 2mA, 0 - 20mA, 0 - 200mA, 0 - 2A and 0 - 20A with Backlight Display , USB Port (Standard) and User Interface Software (Optional), Data Hold, APO, Low Battery Indication, Overload Indication, Strong Rugged Casing with Tilt Stand. With Calibration Certificate with Traceability to NABL Lab will be supplied with every meter.	MIPL	9030 3310	PM-AAC-5R	2970
4	5 Digit DC Multi-Range Ammeter , 0 - 2mA, 0 - 20mA, 0 - 200mA, 0 - 2A and 0 - 20A with Backlight Display , USB Port (Standard) and User Interface Software (Optional), Data Hold, APO, Low Battery Indication, Overload Indication, Strong Rugged Casing with Tilt Stand. With Calibration Certificate with Traceability to NABL Lab will be supplied with every meter.	MIPL	9030 3310	PM-ADC-5R	2880
5	Accessories : Test Lead of 1M (Red & Black for 20A continuous)	MIPL	9033 0000	TEST LEAD FOR 20A AC/DC PORTABLE METER	On Request
6	Accessories : USB Cable	MIPL	9033 0000	USB CABLE FOR PORTABLE METER	On Request
7	Accessories : User Interface Software	MIPL	9033 0000	SOFTWARE FOR PORTABLE METER	On Request
8	Accessories : 6V DC Adapter	MIPL	9033 0000	ADAPTOR FOR PORTABLE METER	On Request

A	Digital Multimeters - Palm / Pocket Size				
1	3 ¾ Digits / 4000 Counts TRMS Autoranging Pocket Size Digital Multimeter with Backlight, Frequency, Capacitance, REL Δ, Diode Test, Audible Continuity, Data Hold and APO functions	MIPL	9030 3100	101P+TRMS	1170
2	3 5/6 Digits / 6000 Counts TRMS Auto Ranging Pocket Size Digital Multimeter with Backlight, Frequency, Capacitance, Temperature, Duty Cycle, NCV, Live Test, REL Δ and APO functions	MIPL	9030 3100	108P+TRMS	On Request
3	3½ Digit / 2000 Counts Digital Mutimeter with Backlight, Audible Continuity, Diode Test, hFE Test and Data Hold Functions	MMPL	9030 3100	DMM 830L (MOQ 10 PCS)	630
4	3½ Digit / 2000 Counts Digital Multimeter with Backlight, Audible Continuity, Diode Test, hFE Test, Data Hold & Battery Test functions	MMPL	9030 3100	63+	855
5	3½ Digit / 2000 Counts Digital Mutimeter with 20A AC/DC, hFE Test, Backlight, Diode Test, Audible Continuity, Data Hold and APO Functions	MMPL	9030 3100	603+	900
6	4 Digit / 9999 Counts TRMS Autoranging Pocket Size Digital Multimeter with Backlight, Frequency, Capacitance, Duty Cycle, Diode Test, Square Wave Output, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	126B+TRMS	2520
7	4 Digit / 9999 Counts TRMS Autoranging Pocket Size Digital Multimeter with Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold, NCV and APO functions	MMPL	9030 3100	135B+TRMS	2979

B	Digital Multimeters - Professional Type				
----------	--	--	--	--	--

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
1	3½ Digit / 2000 Counts Digital Multimeter with Holster + Magnet, Backlight, Torch Light, NCV (LED, Buzzer & EF Strenght), hFE (Transistor Test), Diode Test, Audible Continuity, Data Hold and APO functions	MIPL-T	9030 3100	603 JUNIOR	981
2	3½ Digit / 2000 Counts TRMS Digital Multimeter with 20A AC/DC, Diode & hFE Test, 17mm Large LCD with Backlight, Live Test, Capacitance, Frequency, REL Δ Audible Continuity, Data Hold and APO functions	MIPL	9030 3100	603P+ TRMS	On Request
3	3½ Digit / 6000 Counts TRMS Autoranging Digital Multimeter with Holster + Magnet, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Backlight, Torch Light, APO, NCV (LED, Buzzer & EF Strenght), Diode Test, Audible Continuity, Data Hold and APO functions	MIPL-T	9030 3100	801 JUNIOR	1584
4	3½ Digit / 2000 Counts Autoranging Digital Multimeter with K Type Thermocouple, Temperature, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	9A06	2493
5	3¾ Digit / 4000 Counts Autoranging Digital Multimeter with K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	801AUTO	2682
6	3½ Digit / 6000 Counts TRMS Autoranging Digital Multimeter with Holster, Backlight, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	153B+TRMS	2790
7	3½ Digit / 6600 Counts TRMS Autoranging Digital Multimeter with K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	666TRMS	2736
8	4 Digit / 9999 Counts TRMS Digital Multimeter Digital Dual Display LCD with Auto Backlight, APO, Resistance, Capacitance, hEF, Frequency, Duty Cycle, REL Δ, Data Hold, Max/Min, Peak, Red & Green Light, NCV, Torch Light & Bargraph functions	MIPL-T	9030 3100	45CF+	2907
9	3½ Digit / 6000 Counts TRMS Autoranging Digital Multimeter with Holster, K Type Thermocouple, Temperature, Backlight, Frequency, Capacitance, Duty Cycle, REL Δ, MAX / MIN, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	171B+TRMS	2970
10	4 Digit / 9999 Counts TRMS Auto / Manual Digital Multimeter with Holster, Digital Dual Display LCD with Auto Backlight, APO, Resistance, Capacitance, Frequency, Duty Cycle, REL Δ, Data Hold, Max/Min, Peak, Red & Green Light, NCV, Torch Light & Bargraph functions	MIPL-T	9030 3100	135P+	3186
11	4 Digit / 9999 Counts TRMS Auto / Manual Digital LCR Multimeter with holster Digital Dual Display LCD with Auto Backlight, APO, Resistance, Capacitance, Inductance, Frequency, Duty Cycle, REL Δ, Data Hold, Max/Min, Peak, Red & Green Light, NCV, Torch Light & Bargraph functions	MIPL-T	9030 3100	LCR99	3618
12	4½ Digit / 19999 Counts TRMS Autoranging Digital Multimeter with Backlight, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold, NCV, MIN / MAX, Δ ZERO / REL and APO functions	MMPL	9030 3100	450B+TRMS	3825
13	3½ Digit / 2000 Counts Digital Multimeter with Holster, Automatic Terminal Blocking Mechanism, K Type Thermocouple, Temperature, RPM, Ignition Frequency, MS Pulse Width, Backlight, hFE (Transistor Test), Diode Test, Audible Continuity, Data Hold and APO functions	MIPL-T	9030 3100	6255	4644

C	Digital Clampmeters / Tongtesters (AC) - Small				
1	3½ Digit / 2000 Counts 400A AC TRMS Autoranging Digital Clampmeters with NCV (LED, Buzzer & EF Strenght), Backlight, Diode Test, Data Hold and APO functions	MMPL	9030 3390	2727+	918
2	3½ Digit / 2000 Counts 600A AC TRMS Autoranging Digital Clampmeter with NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Diode Test, Audible Continuity, Data Hold, Max and APO functions	MIPL-T	9030 3390	27-AUTO BL	1377
3	3 ¾ Digit / 4000 Counts 600A AC TRMS Autoranging Digital Clampmeter with NCV (LED, Buzzer & EF Strenght), Backlight, Torchlight, Diode Test, Audible Continuity, Data Hold, Capacitance and APO functions	MIPL-T	9030 3390	54+	1431

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
4	3½ Digit / 2000 Counts 600A AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature, NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Diode Test, Audible Continuity, Data Hold, Max and APO functions	MIPL-T	9030 3390	27T-AUTO BL	1557
5	3½ Digit / 2000 Counts 400A AC Autoranging SMART Digital Clampmeter with AUTO Sensing of ACV, DCV, Resistance, Audible Continuity and Data Hold functions	MMPL	9030 3390	18 SMART	1557
6	3¾ Digit / 4000 Counts 600A AC TRMS Autoranging Digital Clampmeter with NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Frequency, Diode Test, Audible Continuity, Data Hold, REL Test and APO functions	MIPL-T	9030 3390	72-AUTO BL	1773
7	3 ¾ Digit / 4000 Counts 600A AC TRMS Autoranging Digital Clamp Meter with K Type Thermocouple, Temperature, Frequency, NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Diode Test, Data Hold, Capacitance and APO functions	MIPL-T	9030 3390	90+	1800
8	3¾ Digit / 4000 Counts 600A AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature, NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Capacitance, Frequency, Diode Test, Audible Continuity, Data Hold, REL Test and APO functions	MIPL-T	9030 3390	72T-AUTO BL	1971

D	Digital Clampmeters / Tongtesters (AC / TRMS)				
1	3½ Digit / 2000 Counts 1000A AC Manual Ranging Digital Clampmeter with Data Hold, Insulation Test, Resistance and Audible Continuity functions	MMPL	9030 3390	DTT266 (MOQ 10 PCS)	774
2	3½ Digit / 1999 Counts 1000A AC TRMS Manual Ranging Digital Clampmeter Data Hold, Touchlight, Backlight, NCV, (LCD Buzzer & EF Strenght), Live Test, APO Functions.	MMPL	9030 3390	2250 Jr	On Request
3	3½ Digit / 2000 Counts 1000A AC Autoranging Digital Clampmeter with NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, K Type Thermocouple, Temperature, Diode Test, Audible Continuty, Data Hold, MAX and APO functions	MIPL-T	9030 3390	2502T-AUTO BL	2205
4	3½ Digit / 2000 Counts 1000A AC & 1000V AC/DC Digital Clampmeter with Data Hold, Audible Continuity, Diode Test and APO functions	MMPL	9030 3390	3150+	2196
5	3½ Digit / 6000 Counts 1000A AC Autoranging Digital Clampmeter with K Type Thermocouple, Temprature, NCV (LED, Buzzer & EF Strenght), Back Light, Torch Light, Capacitance, Frequency, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MIPL-T	9030 3390	2520THz-AUTO BL	2655
6	3¾ Digit / 4200 Counts 1000A AC TRMS Autoranging Digital Clampmeter with Frequency, Duty Cycle, Diode Test, Audible Continuty, Data Hold and APO functions	MMPL	9030 3390	2250-Hz AUTO	3006
7	3½ Digit / 6000 Counts 1000A AC TRMS Autoranging Digital Clampmeter with µA Range, Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3390	1008-TRMS	4041

E	Digital Clampmeters / Tongtesters (DC / AC) - Small				
1	3 ½ Digit / 6000 Counts 600A DC/AC TRMS Autoranging Digital Clampmeter with Frequency, Capacitance, Duty Cycle, Data Hold, Back Light (White & Orange), Touch Light, NCV (Buzzer & EF strength) and APO functions	MMPL	9030 3900	3690P+ AUTO	On Request
2	3½ Digit / 6000 Counts 600A DC/AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature, Frequency, NCV (LED, Buzzer & EF Strenght), Backlight, Torchlight, Capacitance, Diode Test, Audible Continuity, Data Hold, Hz / Duty, LoZ (DC V / AC V), VFC and APO functions	MIPL-T	9030 3390	99+	3564
3	3½ Digit / 6000 Counts 600A DC/AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature, NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Capacitance, Frequency, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MIPL-T	9030 3390	36-AUTO BL	3744
4	3¾ Digit / 4000 Counts 600A DC/AC Autoranging Digital Clampmeter with Frequency, Duty Cycle, Diode Test, Audible Continuity, Data Hold, Δ Zero Button (for DCA) and APO functions	MMPL	9030 3390	3690 AUTO	4833

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
F	Digital Clampmeters / Tongtesters (DC / AC / TRMS)				
1	3¼ Digit / 4200 Counts 1200A DC / 1000A AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature, Capacitance, Frequency, Duty Cycle, MAX / MIN, Δ REL, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3390	3600+ / 3600BL+	4338
2	3½ Digit / 6000 Counts 1200A DC/AC TRMS Autoranging Digital Clampmeter with μA Range, Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3390	1080-TRMS	5535
3	3¼ Digit / 6000 Counts 2000A DC /2000A AC TRMS Autoranging Clampmeter with 60 Segment Bargraph with Frequency, Capacitance, Duty Cycle, RPM, MIN-MAX, Δ ZERO, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3390	2003A+	7632
4	3½ Digit / 1999 Counts 2000 V & A DC / AC TRMS Auto & Manual Ranging Digital Clampmeter with Backlight, Torchlight, Inrush Current, Capacitance, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3390	4455	8532

G	Analog Insulation Testers				
1	100V - 20MΩ Analog Insulation Tester	MIPL	9030 3390	MC-901	2133
2	500V - 100MΩ Analog Insulation Tester	MIPL	9030 3390	MC-903	2133
3	500V - 500MΩ Analog Insulation Tester	MIPL	9030 3390	MC-904	2133
4	1000V - 200MΩ Analog Insulation Tester	MIPL	9030 3390	MC-906	2133
5	1000V - 500MΩ Analog Insulation Tester	MIPL	9030 3390	MC-907	2133
6	500V - 1000MΩ Analog Insulation Tester	MIPL	9030 3390	MC-941	2367
7	1000V - 2000MΩ Analog Insulation Tester	MIPL	9030 3390	MC-981	2367
8	100V - 20MΩ Analog Insulation Tester with Battery Adaptor	MIPL	9030 3390	MC-901BA	2322
9	500V - 100MΩ Analog Insulation Tester with Battery Adaptor	MIPL	9030 3390	MC-903BA	2322
10	500V - 500MΩ Analog Insulation Tester with Battery Adaptor	MIPL	9030 3390	MC-904BA	2322
11	1000V - 200MΩ Analog Insulation Tester with Battery Adaptor	MIPL	9030 3390	MC-906BA	2322
12	1000V - 500MΩ Analog Insulation Tester with Battery Adaptor	MIPL	9030 3390	MC-907BA	2322
13	500V - 1000MΩ Analog Insulation Tester with Battery Adaptor	MIPL	9030 3390	MC-941BA	2547
14	1000V - 2000MΩ Analog Insulation Tester with Battery Adaptor	MIPL	9030 3390	MC-981BA	2547
15	500V - 100MΩ Analog Insulation Tester (Hand Cranking Type)	MIPL-T	9030 3390	HIT 5 - 1	5040
16	500V - 200MΩ Analog Insulation Tester (Hand Cranking Type)	MIPL-T	9030 3390	HIT 5 - 2	5040
17	1000V - 200MΩ Analog Insulation Tester (Hand Cranking Type)	MIPL-T	9030 3390	HIT 1K - 2	5040
18	1000V - 500MΩ Analog Insulation Tester (Hand Cranking Type)	MIPL-T	9030 3390	HIT 1K - 5	5040
19	2500V - 5000MΩ Analog Insulation Tester (Hand Cranking Type)	MIPL-T	9030 3390	HIT 2K5 - 50	9072
20	5000V - 5000MΩ Analog Insulation Tester (Hand Cranking Type)	MIPL-T	9030 3390	HIT 5K - 50	On Request

H	Digital Insulation Testers				
1	100V - 20MΩ Digital Insulation Tester	MIPL	9030 3390	DIT99BL - A	1926
2	250V - 200MΩ Digital Insulation Tester	MIPL	9030 3390	DIT99BL - B	1926
3	500V - 200MΩ Digital Insulation Tester	MIPL	9030 3390	DIT99BL - C	1926
4	1000V - 200MΩ Digital Insulation Tester	MIPL	9030 3390	DIT99BL - D	1926
5	1000V - 2000MΩ Digital Insulation Tester	MIPL	9030 3390	DIT99BL - E	1926
6	100V - 20MΩ Digital Insulation Tester with Battery Adapter	MIPL	9030 3390	DIT99BL - A (BA)	2106
7	250V - 200MΩ Digital Insulation Tester with Battery Adapter	MIPL	9030 3390	DIT99BL - B (BA)	2106
8	500V - 200MΩ Digital Insulation Tester with Battery Adapter	MIPL	9030 3390	DIT99BL - C (BA)	2106
9	1000V - 200MΩ Digital Insulation Tester with Battery Adapter	MIPL	9030 3390	DIT99BL - D (BA)	2106

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
10	1000V - 2000MΩ Digital Insulation Tester with Battery Adapter	MIPL	9030 3390	DIT99BL - E (BA)	2106
11	1kV - 20GΩ Digital Insulation Tester with P.I., D.A.R. Low Ohms & AC Voltage Functions	MIPL-T	9030 3390	DIT 936PI	4788
12	2.5kV - 200GΩ Digital Insulation Tester with P.I., D.A.R. Low Ohms & AC Voltage Functions	MIPL-T	9030 3390	DIT 945PI	5985
13	2.5kV - 20GΩ Digital Insulation Tester with P.I., D.A.R. and AC / DC Voltage functions	MIPL-T	9030 3390	DIT 918+	6363
14	5kV - 200GOhms Digital Insulation Tester with 6 Ranges	MIPL-T	9030 3390	DIT 954-6R	11853
15	5kV - 200GΩ Digital Insulation Tester with AC Voltage, Phase Sequence and Phase Status Indicator functions	MIPL-T	9030 3390	DIT 954	13248
16	5kV - 10T Ohms Digital Insulation Resistance Tester with P.I. & D.A.R. Measurements, Ramp Test, FR Test, AC / DC Voltage upto 1000V, Capacitance, PC Communication functions	MIPL-T	9030 3390	DIT 5K10T-PI	On Request

I	Digital Earth / Ground Resistance & Leakage Current Testers				
1	Digital Earth Resistance Tester with Earth Voltage and Data Hold functions	MIPL	9030 3390	DET 909	4212
2	Low AC Current Tester upto 10μA AC Resolution , with Large Conductor Diameter (30mm), AC Current (20mA, 200mA, 2A, 60A), ACA, ACV, DCV, Large 3½ Digit LCD (1999), Data Hold, Low Battery Indication and APO functions	MIPL-T	9030 3390	4671A	8982
3	Leakage Current Tester with 10μA AC Ultra High Resolution, AC Current (40mA, 400mA, 4A, 40A, 60A), AC Voltage & Resistance Functions, Jaw Opening : For Cable of 30mm Diameter	MMPL	9030 3390	4671	28197
4	Clamp- On Earth / Ground Resistance (Non Contact Type) with Range 0.01Ω - 500Ω, Data Storage Memory, Data Hold, Autoranging, Auto Power Off Functions, Jaw Opening : For Earthing Strip of 55 x 32 mm	MIPL-T	9030 3390	4680SL	25380
5	Clamp- On Earth / Ground Resistance and Leakage Current tester (Non Contact Type) with Range 0.01Ω - 500Ω, 0.5mA - 20.00A AC , Data Storage Memory, Data Hold, Autoranging, Auto Power Off Functions, Jaw Opening : For Earthing Strip of 55 x 32mm	MIPL-T	9030 3390	4680SLC	29520
6	Clamp - On Earth / Ground Resistance Tester (Non Contact Type) with Range : 0.010Ω - 1000Ω, Data Storage Memory, Data Hold, Autoranging, Auto Power Off functions, Jaw Opening : For Earthing Strip of 65 x 32 mm	MIPL-T	9030 3390	4680BL	34929
7	Clamp - On Earth / Ground Resistance and Leakage Current Tester (Non Contact Type) with Range : 0.010Ω - 1000Ω, 0.5mA - 30.00mA AC, Data Storage Memory, Data Hold, Autoranging, Auto Power Off functions, Jaw Opening : For Earthing Strip of 65 x 32 mm	MIPL-T	9030 3390	4680BLC	39402

J	LCR Meter				
1	LCR Meter , Measures : L, C, R, Z, D, Q, Ø and ESR, Signal Frequency : 100Hz, 120Hz, 1KHz and 10KHz, Test Terminals : 2, 4 and 5 Terminals, USB Interface with Software, Rechargeable Battery and AC Adaptor, Holster, Backlight, Series / Parallel Modes, Manual / Auto, Short / Open, Percentage / MAX / MIN / Average / Data Hold functions	MMPL	9030 3390	LCR999A	31932
2	Accessories : SMD 4 Terminal Kelvin Tweezers for LCR999A	MMPL	9030 9010	SMD 4 TERMINAL KELVIN TWEEZERS FOR LCR 999A	9999

K	Milli - Ohmmeter and Micro - Ohmmeter				
1	Milli - Ohmmeter with PC Interface via RS232 - USB Communication and User Software , Test Current : 5A DC (120mΩ), Four Terminal Kelvin Measurement, Manual / Auto Range, Measurement of Resistive and Inductive Materials, HI / LO / PASS Settings, Memory for 3000 Measurement Data, Programmable HI - LO Alarm with 20 Data Memory, Backlight, Rechargeable Batteries with AC Adaptor, LO Battery Indication, Cable Length Measurement in ft / meters, Data Hold, RS232 - USB Bridge Cable, 1 Set of Kelvin Clips	MMPL	9030 3390	7002	78750

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
2	Micro - Ohmmeter with PC Interface via RS232 - USB Communication and User Software , Test Current : 10A DC (60mΩ), Four Terminal Kelvin Measurement, Manual / Auto Range, Measurement of Resistive and Inductive Materials, HI / LO / PASS Settings, Memory for 3000 Measurement Data, Programmable HI - LO Alarm with 20 Data Memory, Backlight, Rechargeable Batteries with AC Adaptor, LO Battery Indication, Cable Length Measurement in ft / meters, Data Hold, RS232 - USB Bridge Cable, 1 Set of Kelvin Clips	MMPL	9030 3390	7272	135450
3	Accessories : Banana Plug Crocodile Clip Test Lead for 7002 / 7272	MMPL	9030 9010	BANANA PLUG CROCODILE CLIP TEST LEAD FOR 7002 / 7272	1998
4	Accessories : 4 Wire Double Prod Test Lead for 7002 / 7272	MMPL	9030 9010	4 WIRE DOUBLE PROD TEST LEAD FOR 7002 / 7272	6003
5	Accessories : Kelvin Clip Test Leads for 7002 / 7272	MMPL	9030 9010	KELVIN CLIP TEST LEADS FOR 7002 / 7272	6003

L	Transformer Turns Ratio Meter				
1	Transformer Turns Ratio Meter with PC Communication Software , Measurement of 1P / 3P Current / Voltage, Transformer's Turns Ratio, Excitation Voltage, Current, Phase Angle and Deviation. Live Test Points, Short Circuit, Open Circuit, Reverse Polarity. VTR / PTR : 0.8000 - 10000 (Autoranging), CTR : 0.8000 to 2000.0 (Autoranging)	MMPL	9030 3390	TTR 8100	236250

M	Battery Capacity Testers / Battery Meters				
1	Battery / Cell Tester	MIPL-T	9030 3390	BCT36 (MOQ 20PCS)	315
2	Automotive Battery Meter : 2 -200Ah, 2 - 6 - 12V DC , with Internal Resistive Load, Indicates Battery Condition as FULL / NORMAL / RECHARGE / DISCHARGE	MMPL	9030 3390	ABM18	1494
3	Digital Battery Meter : 40 - 200Ah, 6 / 12V DC with Internal DC Voltmeter upto 0 - 19.99V DC and Internal Resistive Load with Built-In Timer and Charging Test, Indicates Battery Condition as GOOD / WEAK / BAD and Auto Data Hold functions	MIPL-T	9030 3390	DBM72	6939
4	Battery Capacity (IR) Meter measures Internal Resistance Range from 19.999m Ohms to 199.99 Ohms and Voltage upto 99.999V DC for all types of Batteries	MIPL-T	9030 3390	BCM 6300	11556
5	Battery Capacity (Impedence) Tester : Upto 500 Ah & 40V DC with PC Communication , with Software, Comparator Function, Measures Online Internal Impedence / Resistance and Open Circuit Voltage for All Types of Batteries	MMPL	9030 3390	6363	89730
6	Battery Capacity (Impedence) Tester with DC Clamp Meter (Adaptor) : Upto 1200 Ah & 60V DC with PC Communication and Software , Comparator Function, Measures Online Internal Impedence / Resistance, Open Circuit Voltage, Load Current, Terminal Temperature and SOC	MMPL	9030 3390	6390	157140
7	Accessories : Alligator Clip Test Leads for 6363	MMPL	9030 9010	TEST LEADS FOR 6363	6606
8	Accessories : Alligator Clip Test Leads for 6390 (4 Jacks)	MMPL	9030 9010	ALLIGATOR CLIP TEST LEADS FOR 6390 (4 JACKS)	15408
9	Accessories : Pin Type Test Leads for 6390 (4 Jacks)	MMPL	9030 9010	PIN TYPE TEST LEADS FOR 6390 (4 JACKS)	15408

N	Automotive Battery Meters				
1	Vehicle Battery System Meter Suitable for 12V DC, 3 to 250Ah Batteries, Measures Battery State (CCA / IR / DC V), CCA Range : 100 - 1700, SOC, SOH, Engine Activation Load Test and Charging Test functions	MIPL-T	9030 3390	VBSM6129B+	2952

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
2	Vehicle Battery System Meter Suitable for 12V DC Batteries , Measures Battery State (CCA / IR / DC V) CCA Range : 100 - 1700, Engine Activation Load Test and Charging Test functions	MIPL-T	9030 3390	VBSM6129B	3753
3	Multifunction Automotive Meter having Combined Functions of Auto Ranging DMM, Power Probe, Logic Probe Test Leads (Both Pinpoint & Hook), Measures AC/DC Voltage, Resistance, Temperature, Flash Light, Data Hold, Continuity and Logic Test functions	MMPL	9030 3390	MAM6138	3807
4	Motorcycle / Two Wheeler / Electrical System Battery Meter suitable for 3 to 20Ah, 9 to 16V DC Batteries , Measures Battery State (CCA / Ah / DC V), Engine Cranking Load Test, SOC, SOH, Charging System Test, Internal Resistance and Battery Condition functions	MIPL-T	9030 3390	MBM27	3852
5	3½ Digit / 2000 Count Digital Multimeter with Holster, Automatic Terminal Blocking Mechanism , K Type Thermocouple, Temperature, RPM, Ignition Frequency, MS Pulse width, Backlight, HFE, Diode Test, Audible Continuity, Data Hold and APO functions	MIPL-T	9030 3390	6255	4644
6	Vehicle Battery System Meter Suitable for 12 and 24 V DC Batteries , Measures Battery State (CCA / IR / DC V) CCA Range : 100 - 1700, Engine Activation Load Test, Maximum Load Test and Charging Test functions	MIPL-T	9030 3390	VBSM6246	5112
7	Vehicle Battery System Meter with Built - In Printer Suitable for 12 and 24 V DC Batteries , Measures Battery State (CCA / IR / DC V) CCA Range : 100 - 1700, Engine Activation Load Test, Maximum Load Test and Charging Test functions	MIPL-T	9030 3390	VBSM6246P	12600

O	Solar Analyzers				
1	Solar Power Meter (Irradiance Meter) with Orientation and Tilt Angle : 0 - 90°, Irradiance Range : 0-2000 W/m2 (0 - 634 BTU / ft2.h) with Data Hold and Backlight Display	MMPL	9031 8000	936	15453
2	Solar Module Analyzer (Photovoltaic I - V Curve Tester) : 60V, 12A (500W Capacity), Measures : Vnow, Voc, Isc, Pmax, VmaxP, ImaxP, Efficiency and Fill Factor with PC Connectivity, Memory Record and Backlight Display	MMPL	9030 3390	9009	157500

PA	Environment Testing Instruments				
1	Long Probe Handy Multi Purpose Thermometer -50° to 300°C / - 58°F to 572°F , °C/°F Selection	MMPL	9025 1990	MTP-9 (MOQ 20 PCS)	360
2	Temperature and Humidity Meter with Clock : -10°C to 50°C / 14°F to 122°F, °C / °F Selection, MAX/MIN, Integral Hour Alarm, Clock and Calendar	MMPL	9025 8090	THM-9 (MOQ 15 PCS)	423
3	Portable / Desk / Wall Mounting Temp. & RH Meter -20°C to 90°C	MMPL	9025 1990	PTHM-90	On Request
4	Desk Temp. & RH Meter With Clock & Calendar -20° to 90°C	MMPL	9025 1990	DTHM-90	On Request
5	Portable / Desk / Wall Mounting Temp. & RH Meter -40°C - 90°C / - 40°F to 194°F	MMPL	9025 1990	PTHM-90C	On Request
6	Digital Sound Level Meter : 35dB - 130dB (31.5 Frequency to 8K Frequency), MAX / MIN / HOLD, Auto Power Off	MMPL	9027 8090	970P	1953
7	Air Flow Anemometer : 1 - 25m/s, 0 to + 50°C, m / Sec, Ft / min, Knots, Km / h, MPH, CFM, MAX / MIN / HOLD, Auto Power Off	MMPL	9030 3390	961P	2520
8	Humidity & Temperature Meter : 0 to 100% RH, - 20 to 80°C, °C / °F / RH Selection, MAX / MIN, Auto Power Off	MMPL	9025 1990	920P	2223
9	Digital LUX Meter (with Flexible Cord Sensor) : 0 - 2,00,000 lux / 0 - 20,000 fc, MAX / MIN, Backlight, Auto Power Off with Disable Function, Data Hold	MMPL	9027 8090	930T	2817
10	Digital LUX Meter : 0 - 2,00,000 lux / 0 - 20,000 fc, MAX / MIN, Backlight, Auto Power Off	MMPL	9027 8090	930P	2817

PB	Environment Testing Instruments (Professional Series)				
1	Humidity and Temperature Meter : 0-100% RH, -20°C to 60°C / -4°F to 140°F, °C / °F Selection, Data Hold, Backlight, Autoranging, Auto Power Off	MMPL	9025 1990	920K	On Request

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
2	LUX Meter : 0 to 2,00,000 Lux / 0 to 20,000 Fc, Autoranging, MIN / MAX, Data Hold, Backlight, Auto Power Off	MMPL	9027 8090	930K	On Request
3	Brake Fluid Tester : Indicates Brake Oil conditions as GOOD / CAUTIONS / STOP, Autoranging, Data Hold, Backlight, Warning Tone, Auto Power Off	MMPL	9031 8000	940K	On Request
4	Combustible Gas Leak Detector : 0 to 9999 PPM / 0 to 20% LEL, MIN / MAX / AVG, Autoranging, Data Hold, Backlight, Auto Power Off	MMPL	9027 0000	950K	On Request
5	Anemometer : 0.80 to 40m/sec, 2.88 to 144km/h, 2.62 to 131.2ft/s, 1.62 to 77.70knots, 1.802 to 90mil/h, 157.52 to 7874 ft/m, Autoranging, MIN / MAX / AVG, Data Hold, Backlight, Auto Power Off	MMPL	9030 3390	961K	On Request
6	Sound Meter : 30dB to 130dB, Frequency 31.5 to 8KHz, MIN / MAX, Data Hold, Backlight, Auto Power Off	MMPL	9027 8090	970K	On Request
7	Tachometer (Contact Type) : 50 to 19999 RPM, m / min, m / sec, ft / min, ft / sec, in / min, Autoranging, MIN / MAX, Data Hold, Backlight, Auto Power Off	MMPL	9029 2090	980K	On Request
8	Tachometer (Non-Contact Type) : 50 to 19999 RPM, 50 to 250mm, m / min, m / sec, ft / min, ft / sec, in / min, Autoranging, MIN / MAX, Data Hold, Backlight, Auto Power Off	MMPL	9029 2090	981K	On Request
9	Coating Thickness Gauge : 0 to 1250µm, 0 to 49.2mil, Autoranging, MIN / MAX / AVG, Data Hold, Backlight, Audio Alarm, Data Storage, Auto Power Off	MMPL	9026 1090	990K	On Request

PC	Infrared Thermometers (Body & Industrial)				
1	Infrared (Body / Forehead) Thermometer : 36°C to 42.9°C / 97°F to 109°F for Body and 0°C to 100°C / 32°F to 212°F for Surface, °C / °F Selection, Green / Orange / Red Backlight to classify level temperature, APO functions	MIPL-T	9025 1990	BT-99	1143
2	Infrared (Body / Forehead) Thermometer : 32°C to 43.0°C / 89.6°F to 109.4°F for Body and 0.0°C to 100.0°C / 32.0°F to 212.0°F for Surface, °C / °F Selection, Green / Orange / Red Backlight to classify level temperature, APO functions	MIPL	9025 1990	MBT-99	1143
3	Infrared Thermometer : -50° to 600°C / -58°F to 1112°F, °C/°F Selection, Backlight, APO Functions	MIPL-T	9025 1990	IRT600TC (MOQ 5 PCS)	1008
4	Infrared Thermometer : -50°C to 1050°C / -58°F to 1922°F, °C / °F Selection, Backlight, MAX / MIN / DIF / AVG / Data Storage, Auto Power Off	MMPL	9025 1990	IRT 1050P	9486

PD	Laser Distance Meters				
1	Laser Distance Meter : 0.05 to 60m, Units : m / in / ft / ft' in", Functions : Addition, Subtraction, Area, Volume, Pythagorean, Data Storage, Backlight, MIN / MAX, Timer, Historical Storage	MMPL	9027 8090	LDM60+	3510
2	Laser Distance Meter : 0.05 to 100m, Units : m / in / ft / ft' in", Functions : Addition, Subtraction, Area, Volume, Pythagorean, Data Storage, Backlight, MIN / MAX, Timer, Historical Storage	MMPL	9027 8090	LDM100+	4122

Q	Power and Harmonics Analyzers / Testers				
1	AC Clamp-On TRMS Power & Harmonics Tester , Measures : V, A, W, PF, Phase Angle, THD upto 99th Order, Crest Factor, Resistance, Continuity, HP, VA, KVA, VAR, KVAh, WH, KWH and Phase Sequence. Jaw Opening : For Cable upto 55mm Diameter / Bus Bar 64 x 24mm.	MMPL	9030 3390	PHT 4545	53397
2	Power and Harmonics Analyzer : Complete Portable Kit consisting of PHA 5850, 3 Pcs (R, Y, B) Clamp-On CT's Set "A" of Range : 1 / 10 / 100A AC, Voltage Test Leads with Crocodile Clips - 4 Pcs (R, Y, B, N), Carrying Bag, 8 Pcs (1.5V DC) Batteries, External DC Adaptor, Software CD, Users & Software Manual, Optical Isolated USB Cable. PHA 5850 Measures : Single / Three Phase System, TRUE RMS Value, Harmonics (V & A) upto 99th Order, THD, Energy, Active / Reactive / Apparent Power, Power Factor, Maximum Demand, Phase Angle, Graphic Phasor Diagram, Waveform with Peak Value. Built in Memory (512K) , Programmable CTR / PTR, User Friendly Software. Jaw Opening : Suitable for Cable / Conductor upto 30mm Diameter	MMPL	9030 3390	PHA 5850A	267120

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
3	Power and Harmonics Analyzer : Complete Portable Kit consisting of PHA 5850, 3 Pcs (R, Y, B) Clamp-On CT's Set "B" Range : 10 / 100 / 1000A AC, Voltage Test Leads with Crocodile Clips - 4 Pcs (R, Y, B, N), Carrying Bag, 8 Pcs (1.5V DC) Batteries, External DC Adaptor, Software CD, Users & Software Manual, Optical Isolated USB Cable. PHA 5850 Measures : Single / Three Phase System, TRUE RMS Value, Harmonics (V & A) upto 99th Order, THD, Energy, Active / Reactive / Apparent Power, Power Factor, Maximum Demand, Phase Angle, Graphic Phasor Diagram, Waveform with Peak Value. Built in Memory (512K) , Programmable CTR / PTR, User Friendly Software. Jaw Opening : Suitable for Cable / Conductor upto 55mm Diameter / Bus Bar 64 x 24mm	MMPL	9030 3390	PHA 5850B	267120
4	Power and Harmonics Analyzer : Complete Portable Kit consisting of PHA 5850, 3 Pcs (R, Y, B) Flexible CT Set "C" Range : 300 / 3000A AC, Voltage Test Leads with Crocodile Clips - 4 Pcs (R, Y, B, N), Carrying Bag, 8 Pcs (1.5V DC) Batteries, External DC Adaptor, Software CD, Users & Software Manual, Optical Isolated USB Cable. PHA 5850 Measures : Single / Three Phase System, TRUE RMS Value, Harmonics (V & A) upto 99th Order, THD, Energy, Active / Reactive / Apparent Power, Power Factor, Maximum Demand, Phase Angle, Graphic Phasor Diagram, Waveform with Peak Value. Built in Memory (512K) , Programmable CTR / PTR, User Friendly Software. Probe Dimensions : Length : 24 Inches / 610 mm, Minimum Bending Diameter : 35mm, Inner Diameter : 160 mm (approx.), Connector Diameter : 23mm, Cable Diameter : 14mm, Cable Length : From Probe to Box : 1700 mm & From Box to Output : 1700mm	MMPL	9030 3390	PHA 5850C	267120
5	Power and Harmonics Analyzer : Complete Portable Kit consisting of PHA 5850, 3 Pcs (R, Y, B) Flexible CT Set "D" Range : 120 / 1200A AC, Voltage Test Leads with Crocodile Clips - 4 Pcs (R, Y, B, N), Carrying Bag, 8 Pcs (1.5V DC) Batteries, External DC Adaptor, Software CD, Users & Software Manual, Optical Isolated USB Cable. PHA 5850 Measures : Single / Three Phase System, TRUE RMS Value, Harmonics (V & A) upto 99th Order, THD, Energy, Active / Reactive / Apparent Power, Power Factor, Maximum Demand, Phase Angle, Graphic Phasor Diagram, Waveform with Peak Value. Built in Memory (512K) , Programmable CTR / PTR, User Friendly Software. Probe Dimensions : Length : 18 Inches / 460 mm, Minimum Bending Diameter : 35 mm, Inner Diameter : 110 mm, Connector Diameter : 23 mm, Cable Diameter : 14 mm, Cable Length : From Probe to Box : 1700 mm & From Box to Output : 1700mm	MMPL	9030 3390	PHA 5850D	267120
6	Clamp-On CT's Suitable for PHA 5850 of Triple Range : 1 / 10 / 100A AC , One Set = 3 Pcs (R, Y, B), Jaw Opening : For Conductor upto 30mm Diameter	MMPL	8504 9090	CT SET A	61425
7	Clamp - On CT's Suitable for PHA 5850 of Triple Range : 10 / 100 / 1000A AC , One Set = 3 Pcs (R, Y, B), Jaw Opening : For Conductor upto 55mm Diameter / 64 x 24mm Busbar (85049090)	MMPL	8504 9090	CT SET B	61425
8	Flexible CT's Suitable for PHA 5850 of Dual Range : 300 / 3000A AC , One Set = 3 Pcs (R, Y, B)	MMPL	8504 9090	CT SET C	61425
9	Flexible CT's Suitable for PHA 5850 of Dual Range: 120 / 1200A AC , One Set = 3 Pcs (R, Y, B)	MMPL	8504 9090	CT SET D	61425
10	Accessories : Cable for Clamp-On CT for PHA 5850	MMPL	9030 9010	CABLE FOR CLAMP-ON CT FOR 5850	3600
11	Accessories : Voltage Test Leads (R,Y,B, N) for PHA 5850	MMPL	9030 9010	VOLTAGE TEST LEADS (R,Y, B,N) FOR 5850	7200
12	Accessories : Alligator Clip (R, Y, B, N) for PHA 5850	MMPL	9030 9010	ALLIGATOR CLIP (R,Y,B,N) FOR 5850	3996

R	Clamp-On Power Meters
----------	------------------------------

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
1	Clamp-On TRMS Power Meter (1000A, 600kW) Autoranging with Dual Display , Automatic Computation of 1Phase and 3Phase (3P3W/3P4W) Parameters. Measures : TRMS AC A, AC / DC V, TRUE Power, HP, KW, KVA, KVAR, HZ, PF, AC Inrush Current, TRMS uA (AC + DC) Phase Angle, 3 Phase Sequence Indicator, Resistance (Continuity), Capacitance, Diode, Temperature, Data Hold and Auto Power Off. Jaw Opening : For Cable / Conductor upto 43mm / Busbar upto 65mm x 16mm	MIPL-T	9030 3390	3510PHW-AUTO	11763
2	Clamp-On TRMS Auto Ranging Power Meter (1000A, 600kW) with kW, kVA, HP, PF, Phase Angle, Frequency, AC+DC, uA, AC A, AC-DC V, Ohm, W, Capacitance, Diode, Temperature with 3 Phase Adapter	MMPL	9030 3390	3510 PHW (WITH ADAPTOR)	17820
3	3 Phase / 1 Phase TRMS Clamp-On Autoranging Power Meter for AC/DC Power Measurement (2000A, 2000kW) with PF, Phase Angle, Frequency & Memory for Recording. Jaw Opening : For Cable of 55mm Diameter / Bus Bar 65 x 24mm	MMPL	9030 3390	4500	47880

S	Calibrating Equipment				
1	Voltage and Current Signal Generator (Pocket size)	MMPL	9030 3390	VCG-09	On Request
2	Multifunction Process Calibrator : Provides Standard Output for mA, mV, V, Resistance, K, J, E, R, B, S, N and T Thermocouples and PT100 (RTD) Thermometer	MMPL	9030 3390	333P+	On Request
3	Multifunction Process Calibrator : Provides Standard Output for mA, mV, V, Frequency, K, J, E and T Thermocouples	MMPL	9030 3390	333	46782
4	Universal Calibrator	MMPL	9030 3390	90A	765450
5	Multifunctional Calibrator	MMPL	9030 3390	90DQ	1370250
6	AC Multifunctional Calibrator	MMPL	9030 3390	90P	1927800
7	Accessories : Standard Current Coil with Input 5A AC / DC (max.), Turn Ratio 100 / 1	MMPL	8504 9090	5A (For 90DQ / 90P)	45378
8	Accessories : Standard Current Coil with Input 10A AC / DC (max.), Turn Ratio 100 / 1	MMPL	8504 9090	10A (For 90P / 90DQ)	45378
9	Accessories : Standard Current Coil with Input 20A AC / DC (max.), Turn Ratio 50 / 1	MMPL	8504 9090	20A (For 90A)	45378
10	Upto 2.5kV - 5GΩ High Voltage Resistance Box having 17 Selectable Fixed Resistance Values	MIPL-T	9030 3390	90DR	95877
11	Upto 5kV - 211.1111110GΩ High Voltage Resistance Box having 10 Adjustable Potentiometric Resistance Values with 4 1/2 Digit Display upto 5000V DC Voltage	MIPL-T	9030 3390	90DR45D	378918

T	Clamp - On CT's and Flexible AC Current Probes (High Current)				
1	Clamp - On CT, Input : 100A AC, Output : 5A AC , Casing : Blue Colour (with Red or Yellow or Blue Colour Sticker Identification), Jaw Opening : Suitable for Conductor upto 50mm Diameter, Output Connection : 2m Leads	MMPL	8504 9090	CCT50 - 100/5A AC	6615
2	Clamp - On CT, Input : 500A AC, Output : 5A AC , Casing : Blue Colour (with Red or Yellow or Blue Colour Sticker Identification), Jaw Opening : Suitable for Conductor upto 50mm Diameter, Output Connection : 2m Leads	MMPL	8504 9090	CCT50 - 500/5A AC	6615
3	Clamp - On CT, Input : 1000A AC, Output : 5A AC , Casing : Blue Colour (with Red or Yellow or Blue Colour Sticker Identification), Jaw Opening : Suitable for Conductor upto 50mm Diameter, Output Connection : 2m Leads	MMPL	8504 9090	CCT50 - 1000/5A AC	6615
4	Clamp - On CT, Input : 2000A AC, Output : 5A AC , Casing : Black Colour (with Red or Yellow or Blue Colour Sticker Identification), Jaw Opening : Suitable for Conductor upto 60mm Diameter, Output Connection : 2m Leads	MMPL	8504 9090	CCT602 - 2000/5A AC	6777
5	Flexible AC Current Probes, Input : 3000A AC @ 50Hz , Output : 300mV AC, ID : Suitable for Cable of 100mm Diameter, Output Connections : 1m Leads, Power Supply : 9V DC	MMPL	8504 9010	FCT100 - 3000A/300mV AC	6930

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
6	Clamp - On CT, Input : 100A AC , Output : 1A AC, Colours : Red or Yellow or Blue, Jaw Opening : Suitable for Conductor upto 15mm Diameter, Output Connection : Safety Sockets Suitable for 4mm Banana Plug	MMPL	8504 9090	M1 - 100/1A AC	On Request
7	Clamp - On CT, Input : 200 or 500 or 1000A AC (Any Single Range) , Colours : Red or Yellow or Blue, Jaw Opening : Suitable for Conductor upto 53mm Diameter, Output Connection : Safety Sockets Suitable for 4mm Banana Plug	MMPL	8504 9090	S (SINGLE RANGE)	On Request
8	Clamp - On CT, Input : 100, 500, 1000A AC (Triple Range in One CT) , Output : 5A AC, Colours : Red or Yellow or Blue, Jaw Opening : Suitable for Conductor upto 53mm Diameter, Output Connection : Safety Sockets Suitable for 4mm Banana Plug	MMPL	8504 9090	S (TRIPLE RANGE)	On Request

U	POWERGUARD				
1	POWERGUARD having Indian Plug - Socket and Backlight to Display TRMS : KW (0.026 - 4.800KW), V (195.0 - 265.0V AC), Frequency, A (0.110 - 20.00A), PF, KVA, KVA _r , KWh, EUT and CO ₂ (kg)	MIPL	9030 3390	PG09 - 20A	2430
2	POWERGUARD having Indian Plug - Socket and Backlight to Display TRMS : KW (0.024 - 1.440KW), V (195.0 - 265.0V AC), Frequency, A (0.100 - 6.000A), PF, KVA, KVA _r , KWh, EUT and CO ₂ (kg)	MIPL	9030 3390	PG09 - 5A	On Request
3	POWERGUARD having Indian Plug - Socket and Backlight to Display TRMS : W (2.400 - 288.0W), V (195.0 - 265.0V AC), Frequency, A (0.010 - 1.200A), PF, VA, VA _r , KWh, EUT and CO ₂ (kg)	MIPL	9030 3390	PG09 - 1A	On Request

V	Phase Sequence Indicator				
1	Phase Sequence Indicator of Voltage Range : 60 - 600V AC, Frequency Range : 40 - 400Hz with LED Indication and Buzzer	MIPL	9030 3390	PSI 2016 (MOQ 5 PCS)	1449
2	Inverter Analyzer	MIPL	9030 3390	IA - S	666

W	Safety Detector				
1	Non - Contact Voltage Detector Range 90 ~ 1000V AC with LED Light / Torch and Audible Sound, CAT III 1000V AC and APO functions	MMPL	9030 3390	NCVD-1000S (MOQ 20 PCS)	234

X	Accessories				
1	Accessories : One Pair of Test Leads Suitable for DMM / DTT	MMPL	9030 9010	TL-DMM / DTT (N) (MOQ 25 PCS)	153
2	Accessories : One Pair of Test Leads Suitable for Insulation Tester MC900 Series / DIT99BL Series	MIPL	9030 9010	TL - IT	198
3	Accessories : K Type Bead Probe (Upto 260 °C) Suitable for use with DTT 2727, 3510PHW etc	MMPL	8533 9000	TPK - B	153
4	Accessories : K Type Stick Probe (Upto 500 °C) Suitable for use with DMM 9A06, DMM 801A _{UTO} etc	MMPL	8533 9000	TP - 02	On Request
5	Accessories : One Pair of Connecting Leads Suitable for Clamp-On CT's (1 Side Banana and 1 Side U Clip) - 2M	MMPL	9030 9010	CONNECTING LEADS FOR CURRENT CLAMPS (1 SIDE BANANA & 1 SIDE U CLIP) - 2M	1539
6	Accessories : One Set of Connecting Leads for Clamp-On CT's (Red x 1 pc, Yellow x 1 pc, Blue x 1 pc and Black x 3 pcs = 6 pcs) with One Side Banana Jack and One Side U Clip	MMPL	9030 9010	CONNECTING LEADS FOR CURRENT CLAMPS (1 SIDE BANANA & 1 SIDE CROCODILE CLIP) - 2M	1539
7	Accessories : One Set of Connecting Leads for Voltage Measurement (Red x 1 pc, Yellow x 1 pc, Blue x 1 pc and Black x 1 pcs = 4 pcs) with One Side Banana Jack and One Side Crocodile Jack	MMPL	9030 9010	CONNECTING LEADS FOR VOLTAGE MEASUREMENT - 2M	1017

Y	Installation Charges				
---	----------------------	--	--	--	--



Price List - Dealer

Effective 1 April 2025 - V.0425



Reliable



Long-Lasting



Affordable



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	UNIT LIST PRICE (₹)
1	Installation and Commissioning Charges per Man Day (To and Fro, Conveyance, Boarding and Lodging Charges extra at Actuals)	MMPL	0044 0233	INSTALLATION & COMMISSIONING CHARGES - PER MAN DAY	3000

ISO 9001-2015 Certified Company

www.mecoinst.com

For MECO INSTRUMENTS PRIVATE LIMITED

Business Terms and Conditions

General

- This Price List supersedes all our previous Price Lists.
- Order to be placed on **MECO INSTRUMENTS PRIVATE LIMITED, EL-01, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai 400 710.**
- All products are guaranteed for 12 months against defective workmanship as per our standard guarantee policy.
- This Price List is subject to Navi Mumbai Jurisdiction only.
- Prices are subject to change without notice.

Commercial & Taxes

- Prices are Ex-Works (Navi Mumbai). Packing, forwarding, freight, insurance, bank charges, overdue interest, wharf-age, demurrage and other incidental expenses shall be extra.
- Minimum order value is Rs. 20000, otherwise handling charges Rs. 200 extra per dispatch.
- Please provide complete specification and reference number with date of our correspondence at the time of placing order.
- **Taxes (GST) :**
For **Maharashtra Sale** : GST @ 18% [CGST @ 9% + SGST @ 9%] extra.
For **Out of Maharashtra Sale** : IGST @ 18% extra.

Please Mention In Your PO

1. GSTIN Number, TIN Number, CIN Number, PAN Number.
2. Buyers Company Name, Billing Address, Contact Person Name and Mobile Number
3. Consignee Company Name, Delivery Address, Contact Person Name and Mobile Number
4. Transport / Freight Details
5. Insurance Details

Registration Details / Numbers

GSTIN	TIN	CIN	PAN	UDYAM
27AAACM2883Q1ZU	27940002826	U33120MH1969PTC014477	AAACM2883Q	MH-33-0032349

Payment and Banking

- 100% payment in advance against Performa Invoice by E-Payment only (vide RTGS / NEFT) prior to dispatch of goods.
- In case of non - standard products or non - familiar customers, the payment terms will be 20% in advance with the order and balance payment against Performa Invoice prior to dispatch of goods.
- Our bank details as below. Kindly inform payment details by E-mail after remitting the payment. Goods will be dispatched within 2 - 3 working days thereafter.

Beneficiary Name	MECO INSTRUMENTS PRIVATE LIMITED	
Bank Name	CANARA BANK, Vashi Branch	
Bank Address	Showroom 1, Ground Floor, Emerald Building, Next to Neel Siddhi Tower, Plot 195B, Sector 12, Vashi, Navi Mumbai - 400703	
A/C Number	0110261020612	
NEFT & IFSC	CNRB0003302	
MICR Code of Bank	400015145	
Account Type	Overdraft Cash Credit / OCC	

Callibration

All Instruments are callibrated through a chain of internal standards which are ultimately traceable to National Standards. However callibration and traceability certificate is issued only against specific requirement at extra charges. Please inform at the time of inquiry / ordering.

All India Service Centre

- Navi Mumbai : **Meco Export Company**, Plot No. EL-60, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai - 400 710 (INDIA) **Tel** : +91-22-27636162 / 07303396162 **E-mail** : service@mecoinst.com

For MECO METERS PRIVATE LIMITED

Business Terms and Conditions

General

- This Price List supersedes all our previous Price Lists.
- Order to be placed on **MECO METERS PRIVATE LIMITED, EL-60, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai 400 710.**
- All products are guaranteed for 12 months against defective workmanship as per our standard guarantee policy.
- This Price List is subject to Navi Mumbai Jurisdiction only.
- Prices are subject to change without notice.

Commercial & Taxes

- Prices are Ex-Works (Navi Mumbai). Packing, forwarding, freight, insurance, bank charges, overdue interest, wharf-age, demurrage and other incidental expenses shall be extra.
- Minimum order value is Rs. 20000, otherwise handling charges Rs. 200 extra per dispatch.
- Please provide complete specification and reference number with date of our correspondence at the time of placing order.
- **Taxes (GST) :**
For **Maharashtra Sale** : GST @ 18% [CGST @ 9% + SGST @ 9%] extra.
For **Out of Maharashtra Sale** : IGST @ 18% extra.

Please Mention In Your PO

1. GSTIN Number, TIN Number, CIN Number, PAN Number.
2. Buyers Company Name, Billing Address, Contact Person Name and Mobile Number
3. Consignee Company Name, Delivery Address, Contact Person Name and Mobile Number
4. Transport / Freight Details
5. Insurance Details

Registration Details / Numbers

GSTIN	TIN	CIN	PAN	UDYAM
27AAACM5996QIZI	27130006327	U331909MH1996PTC104061	AAACM5996Q	MH-33-0093006

Payment and Banking

- 100% payment in advance against Performa Invoice by E-Payment only (vide RTGS / NEFT) prior to dispatch of goods.
- In case of non - standard products or non - familiar customers, the payment terms will be 20% in advance with the order and balance payment against Performa Invoice prior to dispatch of goods.
- Our bank details as below. Kindly inform payment details by E-mail after remitting the payment. Goods will be dispatched within 2 - 3 working days thereafter.

Beneficiary Name	MECO METERS PRIVATE LIMITED	
Bank Name	CANARA BANK, Vashi Branch	
Bank Address	Showroom 1, Ground Floor, Emerald Building, Next to Neel Siddhi Tower, Plot 195B, Sector 12, Vashi, Navi Mumbai - 400703	
A/C Number	0110261020536	
NEFT & IFSC	CNRB0003302	
MICR Code of Bank	400015145	
Account Type	Overdraft Cash Credit / OCC	

Callibration

All Instruments are callibrated through a chain of internal standards which are ultimately traceable to National Standards. However callibration and traceability certificate is issued only against specific requirement at extra charges. Please inform at the time of inquiry / ordering.

All India Service Centre

- Navi Mumbai : **Meco Export Company**, Plot No. EL-60, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai - 400 710 (INDIA) **Tel** : +91-22-27636162 / 07303396162 **E-mail** : service@mecoinst.com



Welcome to MECO



Sales & Marketing Department



Product Display Gallery



Store & Material Handling



SMT & Reflow Machine



Quality Control



Meter Assembly Line



Factory Automation



Environmental & Burn-In Chambers



World Class Calibrating Equipment



Production Line



Vibration Test



Outgoing QC



Training & Seminars



Awards

ISO 9001-2015 Certified Company

MECO INSTRUMENTS PRIVATE LTD.

📍 EL-1, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai - 400710, Maharashtra, INDIA

MECO METERS PRIVATE LTD.

📍 EL-60, MIDC Electronic Zone, TTC Industrial Area, Mahape, Navi Mumbai - 400710, Maharashtra, INDIA



Sales : +91-93233 32435

North India & Goa : +91-93244 11558

South India : +91-93242 89268

East India, M.P. & Gujarat : +91-93244 05281

Maharashtra : +91-93720 11735

Board : +91-90824 11887

Service Centre : +91-73033 96162, +91-22-2763 6162

📧 sales@mecoinst.com 🌐 www.mecoinst.com 🔗 [X](#) [f](#) [in](#) [ig](#)

SCAN ME



Website